

FK KROMBACH Float valve Type: 170 External thread (BSPP)




Characteristics

Type: 170
Norm: EN (DIN)
Housing material: Brass
Material quality: CuZn39Pb2
Surface protection: Nickel-plated
Connection: External thread (BSPP)
Connection 2: Internal thread (BSPP)
Pressure rating: PN6
Face to Face norm: Manufacturer standard
Sealing: EPDM

Characteristics [2]

Material floating rod: 1.4301
Material piston: Brass
Minimum medium temperature (continuous): -10 °C
Maximum medium temperature (continuous): 120 °C
Maximum pressure difference at 20 °C: 6 bar



Nominal inner diameter	Nominal inner diameter 2	With float	Float diameter	Float rod length	Kv value	Article
			mm	mm	m ³ /h	
1/2" [15]	3/8" [10]	No	150	565	2	10051659
3/4" [20]	1/2" [15]	No	150	565	3.5	10051660
1" [25]	3/4" [20]	No	180	670	5.4	10051656
1.1/4" [32]	1" [25]	No	180	670	9.5	10051662
1.1/2" [40]	1.1/4" [32]	No	230	820	13	10051661
2" [50]	1.1/2" [40]	No	230	820	17.4	10051657
2.1/2" [65]	2" [50]	No	245	1050	21	10051663

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.